

Statement of Basis of the Federal Operating Permit

Huntsman Petrochemical LLC

Site/Area Name: F and G Units
Physical location: 2701 Spur 136
Nearest City: Port Neches
County: Jefferson

Permit Number: O1320
Project Type: Renewal

Standard Industrial Classification (SIC) Code: 2869
SIC Name: Industrial Organic Chemicals

This Statement of Basis sets forth the legal and factual basis for the draft permit conditions in accordance with 30 TAC §122.201(a)(4). Per 30 TAC §§ 122.241 and 243, the permit holder has submitted an application under § 122.134 for permit renewal. This document may include the following information:



- A description of the facility/area process description;
- A basis for applying permit shields;
- A list of the federal regulatory applicability determinations;
- A table listing the determination of applicable requirements;
- A list of the New Source Review Requirements;
- The rationale for periodic monitoring methods selected;
- The rationale for compliance assurance methods selected;
- A compliance status; and
- A list of available unit attribute forms.

Prepared on: June 27, 2014

Operating Permit Basis of Determination

Permit Area Process Description

Ethylene oxide is produced by reacting ethylene and oxygen over a silver impregnated catalyst. Two main reactions take place in the reactors:



The first reaction is the desired reaction, and the selectivity is enhanced by injecting ethyl chloride, a reactor inhibitor, into the reactor feed. In each section, ethylene and oxygen are preheated by the reactor effluent in a gas to gas exchanger prior to entering several parallel reactors which facilitate the reaction.

FOPs at Site

The “application area” consists of the emission units and that portion of the site included in the application and this permit. Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). When there is only one area for the site, then the application information and permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: O2286, O2287, O2288, O3056

Major Source Pollutants

The table below specifies the pollutants for which the site is a major source:

Major Pollutants	VOC, SO ₂ , NO _x , HAPs, CO
------------------	---

Reading State of Texas’s Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as “applicable requirements”) that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions
 - Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting
 - Additional Monitoring Requirements
 - New Source Review Authorization Requirements
 - Compliance Requirements
 - Protection of Stratosphere Ozone
 - Permit Location
 - Permit Shield (30 TAC § 122.148)
- Attachments
 - Applicable Requirements Summary

- Unit Summary
 - Applicable Requirements Summary
- Additional Monitoring Requirements
- Permit Shield
- New Source Review Authorization References
- Compliance Plan
- Alternative Requirements
- Appendix A
 - Acronym list

General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

Special Terms and Conditions

Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting. The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a requirement that applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ1 and are not required to be listed separately on a OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

Other conditions. The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

Attachments

Applicable Requirements Summary. The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the “index number,” detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

Additional Monitoring Requirement. The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When

necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

Permit Shield. A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

New Source Review Authorization References. All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified. Units that do not have unit specific applicable requirements other than the NSR authorization do not need to be listed in this attachment. While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

Compliance Plan. A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

Alternative Requirements. This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

Appendix A

Acronym list. This attachment lists the common acronyms used when discussing the FOPs.

Stationary vents subject to 30 TAC Chapter 111, Subchapter A, § 111.111(a)(1)(B) addressed in the Special Terms and Conditions

The site contains stationary vents with a flowrate less than 100,000 actual cubic feet per minute (acfm) and constructed after January 31, 1972 which are limited, over a six-minute average, to 20% opacity as required by 30 TAC § 111.111(a)(1)(B). As a site may have a large number of stationary vents that fall into this category, they are not required to be listed individually in the permit's Applicable Requirement Summary. This is consistent with EPA's White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995, that states that requirements that apply identically to emission units at a site can be treated on a generic basis such as source-wide opacity limits.

Periodic monitoring is specified in Special Term and Condition 3.A. for stationary vents subject to 30 TAC § 111.111(a)(1)(B) to verify compliance with the 20% opacity limit. These vents are not expected to produce visible emissions during normal operation. The TCEQ evaluated the probability of these sources violating the opacity standards and determined that there is a very low potential that an opacity standard would be exceeded. It was determined that continuous monitoring for these sources is not warranted as there would be very limited environmental benefit in continuously monitoring sources that have a low potential to produce

visible emissions. Therefore, the TCEQ set the visible observation monitoring frequency for these sources to once per calendar quarter.

The TCEQ has exempted vents that are not capable of producing visible emissions from periodic monitoring requirements. These vents include sources of colorless VOCs, non-fuming liquids, and other materials that cannot produce emissions that obstruct the transmission of light. Passive ventilation vents, such as plumbing vents, are also included in this category. Since this category of vents are not capable of producing opacity due to the physical or chemical characteristics of the emission source, periodic monitoring is not required as it would not yield any additional data to assure compliance with the 20% opacity standard of 30 TAC § 111.111(a)(1)(B).

In the event that visible emissions are detected, either through the quarterly observation or other credible evidence, such as observations from company personnel, the permit holder shall either report a deviation or perform a Test Method 9 observation to determine the opacity consistent with the 6-minute averaging time specified in 30 TAC § 111.111(a)(1)(B). An additional provision is included to monitor combustion sources more frequently than quarterly if alternate fuels are burned for periods greater than 24 consecutive hours. This will address possible emissions that may arise when switching fuel types.

Federal Regulatory Applicability Determinations

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

Regulatory Program	Applicability (Yes/No)
Prevention of Significant Deterioration (PSD)	No
Nonattainment New Source Review (NNSR)	No
Minor NSR	Yes
40 CFR Part 60 - New Source Performance Standards	Yes
40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs)	Yes
40 CFR Part 63 - NESHAPs for Source Categories	Yes
Title IV (Acid Rain) of the Clean Air Act (CAA)	No
Title V (Federal Operating Permits) of the CAA	Yes
Title VI (Stratospheric Ozone Protection) of the CAA	Yes
CAIR (Clean Air Interstate Rule)	No

Insignificant Activities

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

1. Office activities such as photocopying, blueprint copying, and photographic processes.

2. Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
3. Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
4. Outdoor barbecue pits, campfires, and fireplaces.
5. Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.
6. Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
7. Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.
8. Storage and handling of sealed portable containers, cylinders, or sealed drums.
9. Vehicle exhaust from maintenance or repair shops.
10. Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
11. Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
12. Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.
13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feedwater) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
15. Well cellars.
16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
18. Equipment used exclusively for the melting or application of wax.
19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
20. Shell core and shell mold manufacturing machines.
21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
22. Equipment used for inspection of metal products.
23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
25. Battery recharging areas.
26. Brazing, soldering, or welding equipment.

Determination of Applicable Requirements

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at www.tceq.texas.gov/permitting/air/nav/air_all_ua_forms.html.

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled “Basis of Determination.” Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS). These flowcharts can be accessed via the internet at www.tceq.texas.gov/permitting/air/nav/air_supportsys.html. The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.

The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards, monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column “Changes and Exceptions to RRT.” If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word “None” will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an applicable requirement, it will be explained in detail in the portion of this document entitled “Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected.”

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled “Basis for Applying Permit Shields” specifies which units, if any, have a permit shield.

Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

Determination of Applicable Requirements

Unit ID	Regulation	Index Number	Basis of Determination*
F4TF41	30 TAC Chapter 115, Storage of VOCs	R5112-00a	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
F6TF61	30 TAC Chapter 115, Storage of VOCs	R5112-00a	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
F6TF6101	30 TAC Chapter 115, Storage of VOCs	R5112-00g	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p>
F-F6-147	30 TAC Chapter 115, Storage of VOCs	R5112-009	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>
F-F6-147	40 CFR Part 63, Subpart G	63GT-037	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Enclosed combustion device with a minimum residence time of 0.5 seconds and a minimum temperature of 760° C.</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Design Evaluation Submitted = A design evaluation of the emission control system was submitted to demonstrate compliance with 40 CFR § 63.119(e).
F-F6-148	30 TAC Chapter 115, Storage of VOCs	R5112-009	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>
F-F6-148	40 CFR Part 63, Subpart G	63GT-037	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Enclosed combustion device with a minimum residence time of 0.5 seconds and a minimum temperature of 760° C.</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = A design evaluation of the emission control system was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>
F-F6-149	30 TAC Chapter 115, Storage of VOCs	R5112-009	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>
F-F6-149	40 CFR Part 63, Subpart G	63GT-037	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Enclosed combustion device with a minimum residence time of 0.5 seconds and a minimum temperature of 760° C.</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%. Design Evaluation Submitted = A design evaluation of the emission control system was submitted to demonstrate compliance with 40 CFR § 63.119(e).
F-F6-150	30 TAC Chapter 115, Storage of VOCs	R5112-009	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons Control Device Type = Direct-flame incinerator
F-F6-150	40 CFR Part 63, Subpart G	63GT-037	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Control Device Type = Enclosed combustion device with a minimum residence time of 0.5 seconds and a minimum temperature of 760° C. Emission Control Type = Closed vent system (CVS) and control device (fixed roof) Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%. Design Evaluation Submitted = A design evaluation of the emission control system was submitted to demonstrate compliance with 40 CFR § 63.119(e).
F-P-136	30 TAC Chapter 115, Storage of VOCs	R5112-009	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons Control Device Type = Direct-flame incinerator
F-P-137	30 TAC Chapter 115, Storage of VOCs	R5112-009	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons Control Device Type = Direct-flame incinerator

Unit ID	Regulation	Index Number	Basis of Determination*
F-P-138	30 TAC Chapter 115, Storage of VOCs	R5112-009	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>
F-P-138	40 CFR Part 63, Subpart G	63GT-037	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Enclosed combustion device with a minimum residence time of 0.5 seconds and a minimum temperature of 760° C.</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = A design evaluation of the emission control system was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>
F-P-139	30 TAC Chapter 115, Storage of VOCs	R5112-009	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>
F-P-139	40 CFR Part 63, Subpart G	63GT-037	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Enclosed combustion device with a minimum residence time of 0.5 seconds and a minimum temperature of 760° C.</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Design Evaluation Submitted = A design evaluation of the emission control system was submitted to demonstrate compliance with 40 CFR § 63.119(e).
G1TG1100	30 TAC Chapter 115, Storage of VOCs	R5112-00c	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
G1TG1100	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G1TG15	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G1TG15	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G1TG16	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G1TG16	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G1TG196	30 TAC Chapter 115, Storage of VOCs	R5122-00g	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
G1TG196	40 CFR Part 60, Subpart Kb	60Kb-4	Product Stored = Volatile organic liquid

Unit ID	Regulation	Index Number	Basis of Determination*
			Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
G2TG2111	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G2TG2111	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G2TG2112	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G2TG2112	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G2TG2138	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G2TG2138	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G2TG215	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G2TG215	40 CFR Part 60,	60Kb-3	Product Stored = Volatile organic liquid

Unit ID	Regulation	Index Number	Basis of Determination*
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
G2TG216	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G2TG216	40 CFR Part 60, Subpart Kb	60Kb-3	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
G2TG217	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G2TG217	40 CFR Part 60, Subpart Kb	60Kb-3	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
G3TG31	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G3TG31	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G3TG311	30 TAC Chapter 115, Storage of VOCs	R5112-00c	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
G3TG311	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G3TG312	30 TAC Chapter	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable

Unit ID	Regulation	Index Number	Basis of Determination*
	115, Storage of VOCs		control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G3TG312	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G3TG32	30 TAC Chapter 115, Storage of VOCs	R5112-00c	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
G3TG32	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G3TG38	30 TAC Chapter 115, Storage of VOCs	R5112-00c	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
G3TG38	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G5TG512	30 TAC Chapter 115, Storage of VOCs	R5112-00c	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
G5TG512	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G5TG513	30 TAC Chapter	R5112-00c	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable

Unit ID	Regulation	Index Number	Basis of Determination*
	115, Storage of VOCs		control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
G5TG513	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G5TG514	30 TAC Chapter 115, Storage of VOCs	R5112-00c	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
G5TG514	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G5TG515	30 TAC Chapter 115, Storage of VOCs	R5112-00c	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
G5TG515	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G5TG519	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G5TG519	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G5TG520	30 TAC Chapter	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable

Unit ID	Regulation	Index Number	Basis of Determination*
	115, Storage of VOCs		control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G5TG520	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
G5TG55	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G5TG55	40 CFR Part 60, Subpart Kb	60Kb-4	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
G5TG56	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
G5TG56	40 CFR Part 60, Subpart Kb	60Kb-4	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
G6TG61	30 TAC Chapter 115, Storage of VOCs	R5112-00c	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
G6TG61	40 CFR Part 63, Subpart G	63GT-043	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.

Unit ID	Regulation	Index Number	Basis of Determination*
GRPFGTK1	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
GRPFGTK1	40 CFR Part 60, Subpart Kb	60Kb-22	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>
GRPFGTK2	30 TAC Chapter 115, Storage of VOCs	R5112-00a	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
GRPFGTK3	30 TAC Chapter 115, Storage of VOCs	R5112-00a	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
GRPFGTK3	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
GRPFGTK4	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
GRPFGTK4	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET01	30 TAC Chapter 115, Storage of VOCs	R5112-00g	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p>
RSET01	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET0121	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET0121	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET0132	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET0132	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET0162	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET0162	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET0176	30 TAC Chapter 115, Storage of VOCs	R5112-00a	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
RSET0176	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET0177	30 TAC Chapter 115, Storage of VOCs	R5112-00a	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
RSET0177	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET0186	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET0186	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET02	30 TAC Chapter 115, Storage of VOCs	R5112-00g	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p>
RSET02	40 CFR Part 60, Subpart Kb	60Kb-4	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia</p>
RSET0201	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET0201	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET025	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET025	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET035	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET035	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET036	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET036	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET037	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET037	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET038	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET038	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET05	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET05	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET059	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET059	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET06	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSETo6	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSETo60	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSETo60	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSETo76	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSETo76	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSETo78	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSETo78	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSETo85	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET085	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET086	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET086	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET095	30 TAC Chapter 115, Storage of VOCs	R5112-00g	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p>
RSET095	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSET0178	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
RSET0178	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
T-G3-9	30 TAC Chapter 115, Storage of VOCs	R5112-00c	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
T-G3-9	40 CFR Part 63, Subpart G	63GT-043	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
RSELD5	40 CFR Part 63, Subpart Y	63Y-005	<p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.</p> <p>Material Loaded = Material other than crude oil or gasoline.</p> <p>HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.</p> <p>Source Emissions = Source with emissions less than 10 and 25 tons.</p>
RSELRBMT5	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-018	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p>
RSELRBMT5	40 CFR Part 63, Subpart G	63GL-0g2a	<p>Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.</p>
RSELRBMTD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-018	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p>
RSELRBMTD	40 CFR Part 63, Subpart G	63GL-0g2a	<p>Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.</p>
RSELRBMTW	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-018	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
RSELRBMTW	40 CFR Part 63, Subpart G	63GL-og2a	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.
RSELRPRDC	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-00k	Chapter 115 Control Device Type = No control device. Chapter 115 Facitliy Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected. Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline. Transfer Type = Only loading. True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia. Daily Throughput = Loading greater than or equal to 20,000 gallons per day. Control Options = Pressurized loading system.
RSELRPRDC	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-018	Chapter 115 Facitliy Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline. Transfer Type = Only loading. True Vapor Pressure = True vapor pressure less than 0.5 psia.
RSELRPRDC	40 CFR Part 63, Subpart G	63GL-og2a	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.
RSELRTRKW	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-00c	Chapter 115 Control Device Type = No control device. Chapter 115 Facitliy Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected. Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline. Transfer Type = Only loading. True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia. Daily Throughput = Loading greater than or equal to 20,000 gallons per day. Control Options = Vapor balance system.
RSELRTRKW	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-018	Chapter 115 Facitliy Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline. Transfer Type = Only loading.

Unit ID	Regulation	Index Number	Basis of Determination*
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
RSELRTRKW	40 CFR Part 63, Subpart G	63GL-og2a	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.
F4FUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
F4FUG	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
F6FUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
F6FUG	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
G1FUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
G1FUG	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
G2FUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
G2FUG	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
G3FUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
G3FUG	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
G4FUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
G4FUG	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
G5FUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
G5FUG	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
G6FUG	30 TAC Chapter 115, Pet. Refinery	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.

Unit ID	Regulation	Index Number	Basis of Determination*
	& Petrochemicals		
G6FUG	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
GRPFGFU1	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
GRPFGFU1	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
RSEFUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
RSEFUG	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
F4FF4135	30 TAC Chapter 115, Vent Gas Controls	R5121-10	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies one of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F4FF4135	40 CFR Part 63, Subpart G	63GV-100	<p>Control Device = No recovery device.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent is a Group 2 process vent.</p> <p>Regulation = Owner or operator is electing to comply with the associated monitoring, testing, recordkeeping, and reporting requirements of 40 CFR Part 60, Subpart III, supporting the control requirements of 40 CFR § 60.662.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Electing Control = Not electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) or (a)(2).</p> <p>NSPS TRE Index Value = TRE index value is greater than 8 as calculated using the appropriate equation from 40 CFR Part 60, Subparts III, NNN or RRR.</p> <p>MACT TRE Index Value = TRE index value is greater than 4.0 as calculated using the procedures of 40 CFR § 63.115(d).</p>
F6FF6104	30 TAC Chapter 115, Vent Gas Controls	R5121-10	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies one of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies one of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F6FF6104	40 CFR Part 63, Subpart G	63GV-100	<p>Control Device = No recovery device.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent is a Group 2 process vent.</p> <p>Regulation = Owner or operator is electing to comply with the associated monitoring, testing, recordkeeping, and reporting requirements of 40 CFR Part 60, Subpart III, supporting the control requirements of 40 CFR § 60.662.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Electing Control = Not electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) or (a)(2).</p> <p>NSPS TRE Index Value = TRE index value is greater than 8 as calculated using the appropriate equation from 40 CFR Part 60, Subparts III, NNN or RRR.</p> <p>MACT TRE Index Value = TRE index value is greater than 4.0 as calculated using the procedures of 40 CFR § 63.115(d).</p>
FC4300	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
FC4300	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
FC6300	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
FC6300	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F4-135	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F4-135	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F4-142	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F4-142	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F4-33	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F4-33	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F4-45	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F4-45	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F4-54	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F4-54	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F4-56	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F4-56	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F4-57	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F4-57	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F4-81	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F4-81	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F4-82	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F4-82	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F4-83	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F4-83	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F4-84	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F4-84	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F4-88	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F4-88	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F6-104	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-104	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F6-105	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-105	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.
F-F6-106	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-106	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F6-126	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-126	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F6-33	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-33	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
F-F6-44	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-44	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F6-45	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
F-F6-45	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F6-54	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-54	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F6-56	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-56	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F6-84	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-84	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F6-85	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-85	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F6-86	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-86	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F6-87	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-87	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F6-88	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-88	40 CFR Part 63, Subpart G	63GV-o82N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-F6-95	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-F6-95	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F-G1-106	30 TAC Chapter 115, Vent Gas Controls	R5121-10	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is less than 0.011 scm/min or the VOC concentration is less than 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = No control device</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>VOC Concentration = VOC concentration is less than 612 ppmv.</p>
F-G3-18	30 TAC Chapter 115, Vent Gas Controls	R5121-9	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies one of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies one of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p>
F-G3-18	40 CFR Part 63, Subpart G	63GV-100	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent is a Group 2 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>NSPS TRE Index Value = TRE index value is greater than 8 as calculated using the appropriate equation from 40 CFR Part 60, Subparts III, NNN or RRR.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p> <p>MACT TRE Index Value = TRE index value is greater than 4.0 as calculated using the procedures of 40 CFR § 63.115(d).</p> <p>Plant Type = Vinyl chloride plant.</p>
F-G4-3	30 TAC Chapter 115, Vent Gas Controls	R5121-10	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies one of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>VOC Concentration = VOC concentration is less than 612 ppmv.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
F-G4-5	30 TAC Chapter 115, Vent Gas Controls	R5121-10	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is less than 0.011 scm/min or the VOC concentration is less than 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-G6-11	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
F-G6-11	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
GRPFGVE3	30 TAC Chapter	R5121-2	Alternate Control Requirement = Alternate control is not used.

Unit ID	Regulation	Index Number	Basis of Determination*
	115, Vent Gas Controls		<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
GRPFGVE3	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
GRPFGVE4	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
GRPFGVE4	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
GRPFGVE5	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
GRPFGVE5	40 CFR Part 63, Subpart G	63GV-082N	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
GRPFGVE6	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
GRPFGVE6	40 CFR Part 63, Subpart G	63GV-082R	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>
F4FF4135	40 CFR Part 60, Subpart NNN	60NNN-008a	<p>40 CFR 60 (NSPS) SUBPART NNN CHEMICALS = DISTILLATION UNIT PRODUCES ANY CHEMICAL LISTED IN 40 CFR § 60.667 AS A PRODUCT, CO-PRODUCT, BY-PRODUCT, OR INTERMEDIATE</p> <p>TOTAL RESOURCE EFFECTIVENESS (TRE) [NSPS NNN] = > 8.0 NOT FROM HALOGENATED VENT STREAM</p> <p>CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE [NSPS NNN] = AFTER DECEMBER 30, 1983</p> <p>VENT TYPE [NSPS NNN] = NOT DISCHARGING A VENT STREAM TO A VRS</p> <p>DISTILLATION UNIT TYPE (NSPS NNN) = DOES NOT QUALIFY FOR ANY EXEMPTION IN § 60.660(C)(1)-(3)</p>
F6FF6104	40 CFR Part 60, Subpart NNN	60NNN-008a	<p>40 CFR 60 (NSPS) SUBPART NNN CHEMICALS = DISTILLATION UNIT PRODUCES ANY CHEMICAL LISTED IN 40 CFR § 60.667 AS A PRODUCT, CO-PRODUCT, BY-PRODUCT, OR INTERMEDIATE</p> <p>TOTAL RESOURCE EFFECTIVENESS (TRE) [NSPS NNN] = > 8.0 NOT FROM HALOGENATED VENT STREAM</p> <p>CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE [NSPS NNN] = AFTER DECEMBER 30, 1983</p> <p>VENT TYPE [NSPS NNN] = NOT DISCHARGING A VENT STREAM TO A VRS</p> <p>DISTILLATION UNIT TYPE (NSPS NNN) = DOES NOT QUALIFY FOR ANY EXEMPTION IN § 60.660(C)(1)-(3)</p>
F-G4-3	40 CFR Part 60, Subpart NNN	60NNN-033a	<p>40 CFR 60 (NSPS) SUBPART NNN CHEMICALS = DISTILLATION UNIT PRODUCES ANY CHEMICAL LISTED IN 40 CFR § 60.667 AS A PRODUCT, CO-PRODUCT, BY-PRODUCT, OR INTERMEDIATE</p> <p>TOTAL RESOURCE EFFECTIVENESS (TRE) [NSPS NNN] = > 8.0 NOT FROM HALOGENATED VENT STREAM</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE [NSPS NNN] = AFTER DECEMBER 30, 1983</p> <p>VENT TYPE [NSPS NNN] = DISCHARGING TO A VRS</p> <p>DISTILLATION UNIT TYPE (NSPS NNN) = DOES NOT QUALIFY FOR ANY EXEMPTION IN § 60.660(C)(1)-(3)</p>
GRPFGPRO1	40 CFR Part 63, Subpart F	63F-009	<p>Applicable Chemicals = THE CHEMICAL MANUFACTURING PROCESS UNIT MANUFACTURES, AS A PRIMARY PRODUCT, ONE OR MORE OF THE CHEMICALS LISTED IN 40 CFR § 63.100(B)(1)(I) OR 40 CFR § 63.100(B)(1)(II)</p> <p>Intervening Cooling Fluid = THERE IS NOT AN INTERVENING COOLING FLUID (CONTAINING LESS THAN 5 PERCENT BY WEIGHT OF TOTAL HAPS LISTED IN TABLE 4 OF 40 CFR PART 63, SUBPART F) BETWEEN THE PROCESS AND COOLING WATER</p> <p>Table 2 HAP = THE CHEMICAL MANUFACTURING PROCESS UNIT USES AS A REACTANT OR MANUFACTURES, AS A PRODUCT OR CO-PRODUCT, ONE OR MORE OF THE ORGANIC HAZARDOUS AIR POLLUTANTS (HAPS) IN TABLE 2</p> <p>Table 4 HAP Content = A RECIRCULATING HEAT EXCHANGE SYSTEM IS NOT USED TO COOL PROCESS FLUIDS THAT CONTAIN LESS THAN 5 PERCENT BY WEIGHT OF TOTAL HAPS LISTED IN TABLE 4 OF TITLE 40 CFR PART 63, SUBPART F</p> <p>Alternate Means of Emission Limitation = AN ALTERNATIVE MEANS OF EMISSION LIMITATION IS NOT USED TO ACHIEVE A REDUCTION IN ORGANIC HAP EMISSION</p> <p>NPDES Permit = HEAT EXCHANGE SYSTEM IS NOT SUBJECT TO A NPDES PERMIT WITH ALLOWABLE DISCHARGE LIMIT</p> <p>Meets 40 CFR 63.104(a)(4)(i)-(iv) = HEAT EXCHANGER NOT REQUIRED TO MEET THIS CITATION</p> <p>Heat Exchange System = A HEAT EXCHANGE SYSTEM IS USED</p> <p>Table 9 HAP Content = ONCE-THROUGH HEAT EXCHANGE SYSTEM IS NOT USED TO COOL PROCESS FLUIDS THAT CONTAIN LESS THAN 5 PERCENT BY WEIGHT OF TOTAL HAPS LISTED IN TABLE 9 OF 40 CFR PART 63, SUBPART G</p> <p>Cooling Water Monitored = COOLING WATER IS BEING MONITORED FOR THE PRESENCE OF ONE OR MORE HAPS OR OTHER REPRESENTATIVE SUBSTANCES WHOSE PRESENCE IN COOLING WATER INDICATES A LEAK</p> <p>Cooling Water Pressure = THE HEAT EXCHANGE SYSTEM IS NOT OPERATED WITH THE MINIMUM PRESSURE ON THE COOLING WATER SIDE AT LEAST 35 KILOPASCALS GREATER THAN THE MAXIMUM PRESSURE ON THE PROCESS SIDE</p>

* - The “unit attributes” or operating conditions that determine what requirements apply

NSR Versus Title V FOP

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

NSR Permit	Federal Operating Permit(FOP)
Issued Prior to new Construction or modification of an existing facility	For initial permit with application shield, can be issued after operation commences; significant revisions require approval prior to operation.
Authorizes air emissions	Codifies existing applicable requirements, does not authorize new emissions
Ensures issued permits are protective of the environment and human health by conducting a health effects review and that requirement for best available control technology (BACT) is implemented.	Applicable requirements listed in permit are used by the inspectors to ensure proper operation of the site as authorized. Ensures that adequate monitoring is in place to allow compliance determination with the FOP.
Up to two Public notices may be required. Opportunity for public comment and contested case hearings for some authorizations.	One public notice required. Opportunity for public comments. No contested case hearings.
Applies to all point source emissions in the state.	Applies to all major sources and some non-major sources identified by the EPA.
Applies to facilities: a portion of site or individual emission sources	One or multiple FOPs cover the entire site (consists of multiple facilities)
Permits include terms and conditions under which the applicant must construct and operate its various equipment and processes on a facility basis.	Permits include terms and conditions that specify the general operational requirements of the site; and also include codification of all applicable requirements for emission units at the site.
Opportunity for EPA review for Federal Prevention of Significant Deterioration (PSD) and Nonattainment (NA) permits for major sources.	Opportunity for EPA review, Affected states review, and a Public petition period for every FOP.
Permits have a table listing maximum emission limits for pollutants	Permit has an applicable requirements table and Periodic Monitoring (PM) / Compliance Assurance Monitoring (CAM) tables which document applicable monitoring requirements.
Permits can be altered or amended upon application by company. Permits must be issued before construction or modification of facilities can begin.	Permits can be revised through several revision processes, which provide for different levels of public notice and opportunity to comment. Changes that would be significant revisions require that a revised permit be issued before those changes can be operated.
NSR permits are issued independent of FOP requirements.	FOP are independent of NSR permits, but contain a list of all NSR permits incorporated by reference

New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. These permits can be found in the main TCEQ file room, located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. The Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. The following table specifies the permits by rule that apply to the site. All current permits by rule are contained in Chapter 106. Outdated 30 TAC Chapter 106 permits by rule may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/old106list/index106.html

Outdated Standard Exemption lists may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/oldselist/se_index.html

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 36646	Issuance Date: 02/18/2010
Authorization No.: 5807A	Issuance Date: 02/18/2010
Authorization No.: 5952A	Issuance Date: 02/18/2010
Authorization No.: 5972A	Issuance Date: 02/18/2010
Authorization No.: 647B	Issuance Date: 04/18/2012
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.261	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 09/04/2000
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.264	Version No./Date: 09/04/2000
Number: 106.355	Version No./Date: 11/01/2001
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.433	Version No./Date: 09/04/2000
Number: 106.452	Version No./Date: 09/04/2000
Number: 106.472	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/04/2000
Number: 51	Version No./Date: 09/13/1993
Number: 51	Version No./Date: 10/04/1995

Emission Units and Emission Points

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sandblasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the “Maximum Allowable Emission Rate Table”, or “MAERT” for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

Monitoring Sufficiency

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a relevant time period that are representative of the emission unit’s compliance with the applicable emission limitation or standard. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected

Compliance Assurance Monitoring (CAM):

Compliance Assurance Monitoring (CAM) is a federal monitoring program established under Title 40 Code of Federal Regulations Part 64 (40 CFR Part 64).

Emission units are subject to CAM requirements if they meet the following criteria:

1. the emission unit is subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement;
2. the emission unit uses a control device to achieve compliance with the emission limitation or standard specified in the applicable requirement; and
3. the emission unit has the pre-control device potential to emit greater than or equal to the amount in tons per year for a site to be classified as a major source.

The following table(s) identify the emission unit(s) that are subject to CAM:

Unit/Group/Process Information	
ID No.: GRPFGVE3	
Control Device ID No.: F4HF41	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.121(a)(2)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the firebox temperature is less than 1704 degree Fahrenheit while waste gas is vented to the incinerator.	
Basis of CAM: It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: GRPFGVE4	
Control Device ID No.: F4HF41	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.121(a)(2)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the firebox temperature is less than 1704 degree Fahrenheit while waste gas is vented to the incinerator.	
Basis of CAM: It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: GRPFGVE5	
Control Device ID No.: F6HF61	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.121(a)(2)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the firebox temperature is less than 1737 degree Fahrenheit while waste gas is vented to the incinerator.	
Basis of CAM: It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: GRPFGVE6	
Control Device ID No.: F6HF61	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.121(a)(2)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the firebox temperature is less than 1737 degree Fahrenheit while waste gas is vented to the incinerator.	
Basis of CAM: It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Compliance Review

1. In accordance with 30 TAC Chapter 60, the compliance history was reviewed on May 16, 2014.
2. The compliance history review evaluated the period from 4/23/2009 to 4/22/2014.
Site rating: 2013; Satisfactory Company rating: 17.06; Satisfactory
(High < 0.10; Satisfactory > 0.10 and < 55; Unsatisfactory > 55)
3. Has the permit changed on the basis of the compliance history or site/company rating?No

Site/Permit Area Compliance Status Review

1. Were there any out-of-compliance units listed on Form OP-ACPS?No
2. Is a compliance plan and schedule included in the permit?.....No

Available Unit Attribute Forms

OP-UA1 - Miscellaneous and Generic Unit Attributes
OP-UA2 - Stationary Reciprocating Internal Combustion Engine Attributes
OP-UA3 - Storage Tank/Vessel Attributes
OP-UA4 - Loading/Unloading Operations Attributes
OP-UA5 - Process Heater/Furnace Attributes
OP-UA6 - Boiler/Steam Generator/Steam Generating Unit Attributes
OP-UA7 - Flare Attributes
OP-UA8 - Coal Preparation Plant Attributes
OP-UA9 - Nonmetallic Mineral Process Plant Attributes
OP-UA10 - Gas Sweetening/Sulfur Recovery Unit Attributes
OP-UA11 - Stationary Turbine Attributes
OP-UA12 - Fugitive Emission Unit Attributes
OP-UA13 - Industrial Process Cooling Tower Attributes
OP-UA14 - Water Separator Attributes
OP-UA15 - Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes
OP-UA16 - Solvent Degreasing Machine Attributes
OP-UA17 - Distillation Unit Attributes
OP-UA18 - Surface Coating Operations Attributes
OP-UA19 - Wastewater Unit Attributes
OP-UA20 - Asphalt Operations Attributes
OP-UA21 - Grain Elevator Attributes
OP-UA22 - Printing Attributes
OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes
OP-UA25 - Synthetic Fiber Production Attributes
OP-UA26 - Electroplating and Anodizing Unit Attributes
OP-UA27 - Nitric Acid Manufacturing Attributes
OP-UA28 - Polymer Manufacturing Attributes
OP-UA29 - Glass Manufacturing Unit Attributes
OP-UA30 - Kraft, Soda, Sulfite, and Stand-Alone Semichemical Pulp Mill Attributes
OP-UA31 - Lead Smelting Attributes
OP-UA32 - Copper and Zinc Smelting/Brass and Bronze Production Attributes
OP-UA33 - Metallic Mineral Processing Plant Attributes
OP-UA34 - Pharmaceutical Manufacturing
OP-UA35 - Incinerator Attributes
OP-UA36 - Steel Plant Unit Attributes
OP-UA37 - Basic Oxygen Process Furnace Unit Attributes
OP-UA38 - Lead-Acid Battery Manufacturing Plant Attributes
OP-UA39 - Sterilization Source Attributes
OP-UA40 - Ferroalloy Production Facility Attributes
OP-UA41 - Dry Cleaning Facility Attributes

OP-UA42 - Phosphate Fertilizer Manufacturing Attributes
OP-UA43 - Sulfuric Acid Production Attributes
OP-UA44 - Municipal Solid Waste Landfill/Waste Disposal Site Attributes
OP-UA45 - Surface Impoundment Attributes
OP-UA46 - Epoxy Resins and Non-Nylon Polyamides Production Attributes
OP-UA47 - Ship Building and Ship Repair Unit Attributes
OP-UA48 - Air Oxidation Unit Process Attributes
OP-UA49 - Vacuum-Producing System Attributes
OP-UA50 - Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur Recovery Plant Attributes
OP-UA51 - Dryer/Kiln/Oven Attributes
OP-UA52 - Closed Vent Systems and Control Devices
OP-UA53 - Beryllium Processing Attributes
OP-UA54 - Mercury Chlor-Alkali Cell Attributes
OP-UA55 - Transfer System Attributes
OP-UA56 - Vinyl Chloride Process Attributes
OP-UA57 - Cleaning/Depainting Operation Attributes
OP-UA58 - Treatment Process Attributes
OP-UA59 - Coke By-Product Recovery Plant Attributes
OP-UA60 - Chemical Manufacturing Process Unit Attributes
OP-UA61 - Pulp, Paper, or Paperboard Producing Process Attributes
OP-UA62 - Glycol Dehydration Unit Attributes
OP-UA63 - Vegetable Oil Production Attributes